

Tubular Motor (230V 50Hz)

		Rated Torque (N.m)	Rated Speed (rpm)	Tube Diameter (mm)	Rated Voltage (V)	Rated Frequency (Hz)	Rated Power Input (W)	Rated Current (A)	Running Time (min)	Degree of Protection (IP)	Max Number of Turns (turn)	L1/L2 (mm)
PM35S Standard	PM35S315-3/28	3	28	35	230	50	125	0.52	4	IP44	39	540/527
	PM35S315-6/14	6	14	35	230	50	130	0.53	4	IP44	39	540/527
	PM35S315-6/28	6	28	35	230	50	160	0.66	4	IP44	39	540/527
	PM35S315-10/17	10	17	35	230	50	160	0.66	4	IP44	39	540/527



		(N.m)	(rpm)	(mm)	(V)	(Hz)	(W)	(A)	(min)	(IP)	(turn)	(mm)
PM45S Standard	PM45S415-10/15	10	15	45	230	50	146	0.63	4	IP44	25	524/509
	PM45S415-20/15	20	15	45	230	50	205	0.92	4	IP44	25	524/509
	PM45S415-20/30	20	30	45	230	50	292	1.29	4	IP44	45	585/570
	PM45S415-30/15	30	15	45	230	50	230	1.10	4	IP44	25	585/570
	PM45S415-40/15	40	15	45	230	50	292	1.29	4	IP44	25	585/570
	PM45S415-50/12	50	12	45	230	50	308	1.41	4	IP44	25	585/570



		(N.m)	(rpm)	(mm)	(V)	(Hz)	(W)	(A)	(min)	(IP)	(turn)	(mm)
PM59S Standard	PM59S510-60/15	60	15	59	230	50	370	1.60	4	IP44	21	620/590
	PM59S510-80/15	80	15	59	230	50	430	2.00	4	IP44	21	620/590
	PM59S510-100/12	100	12	59	230	50	491	2.32	4	IP44	21	620/590



Also available 110v 60Hz